



ULTRALOW POWER 24-BIT MARINE SEISMIC DATA LOGGER DAS6502



DAS6502 is a member of **6500** series of *ultralow power, robust, high-performance, extremely versatile 24-bit seismic data recorders and digitizers.*

- A very low-power, high-performance DSP that controls the data acquisition, real-time digitization and filtration, and stores the data temporarily in
 - A micro-power, large capacity CMOS static RAM.
 - A powerful, fully featured single-board PC that controls the data transfer to disk and communication functions. It is active only when the SRAM is full, typically a few minutes a day.
- PMD's proprietary True Real Time™ system, controlled by the DSP, that maintains extremely accurate time.

In such a configuration, the more power hungry components (PC, disk) operate on an extremely low duty cycle, allowing the system to use just about **600 mW** of power.

- .

In such a configuration, the more power hungry components (PC, disk, GPS) operate on an extremely low duty cycle, allowing the system to use *less than 3/4 Watt* of power. The presence of a powerful PC (a single board PC/104 format), however, opens a wide range of options to the user. While the basic **DAS6501** application uses DOS, the PC/104 can be configured with more advanced operating systems, such as WINDOWS. Also, the industry standard PC/104 allows the use of many peripherals in a modular, stackable format, *e.g.*: Ethernet cards, wireless LAN cards, satellite communication hardware, *etc.*

DIGITIZER

Converter Type:	24-bit Δ - Σ ; 320 kHz Base Rate
Dynamic Range:	>130 dB @ 200 sps (rms to FS)
Data Channels:	3 (4) ¹ ; opt. up to 16; Differential <i>or</i> Single-Ended
Sampling Rates:	0.1, 1, 10, 20, 40, 80, 100, 200, 500, 1000, 2000, 4000 sps ²
CMR @ 50, 60 Hz	120dB
Analog Anti-Aliasing Filter:	>100 dB @ primary sampling rate
Digital Filter (@ output Nyquist):	>140 dB @ 200 sps (FIR or opt. IIR)
Programmable Gains:	1,2,4,8,16,32,64
Differential Input Signal Range:	Programmable: ± 2.5 , ± 10 , ± 20 V
Input Impedance	± 2.5 V – 1M Ω ; ± 10 , ± 20 V – 300k Ω
Overvoltage Prot.	± 40 V
State-of-Health Channels:	4 multiplexed inputs; 24-bit resolution
Static RAM Buffer:	Up to 8MB

TIMING SYSTEM

Type:	PLL controlled, GPS-referenced
Max. Accy (Software Selectable):	<1 μ sec
Crystal Frequency Correction Resolution	0.016 ppm
GPS Duty Cycle (User Selectable):	Once every 18 hrs to achieve <1msec accuracy

EVENT DETECTORS

Type:	STA/LTA, up to 6 independent detectors in frequency domain
Pre-filter	Up to 6 passbands
Pre-event data buffer	up to 90 seconds (@ 100 sps)
Trigger channels	May be controlled by one, several or all 6 detectors associated with any physical or virtual acquisition channel

POWER

Voltage:	6 – 16 Vdc
Overvoltage protection:	± 60 V
Power consumption	~0.75W (4 channels, 100 sps)

¹ Fourth channel may be used as state-of-health channel or function as fully featured data channel

² The sampling rate of 4000sps is sustainable for max 5 channels; 2000 sps – for up to 10 channels, and 1000sps – for up to 16.

Specifications subject to change without notice
 105-F West Dudleytown Road, Bloomfield, CT 06002 **USA**
 Tel: 1-860-242-8177 Fax: 1-860-242-7812

e- mail:sales@pmdsci.com Web Site: www.pmdsci.com

USER INTERFACE

Display Type:	Backlit 7" VGA LCD display
Keypad:	12 (numerical + function) keys; optional PC keyboard
User Control:	Menu-driven; state-of-health messaging
Data display:	Up to 3 channels simultaneously
Master Computer	Fully PC Compatible, single-board
Remote PC:	RS232

MASS STORAGE

Miniature Hard Disk	Up to 30 GB, Hot-swappable EIDE Or CFC card up to 8GB
Disk Compatibility:	Any PC
Disk cartridge	80x140x22mm; 190g
Temperature Range:	-30 to +50°C (with industrial grade CFC or opt. built-in heater for HDD)
Data Formats:	Mini-SEED w/Steim-2 compression CSS 3.0: long integer; separate data description in ASCII

COMMUNICATION

Continuous Data Retrieval:	Via RS485 DSP port (up to 1km)
Dial-up Phone Access	RS232; optional internal modem
Ethernet	Optional LAN/wireless LAN card

ENVIRONMENTAL

Housing	Reinforced Plastic
Waterproofing	Fully Submersible to 1m depth
Operating T° Range	-30 to +50°C (with industrial grade CFC or opt. built-in heater for DD)
Humidity	100%
Storage T° Range	-40 to +60°C
Size	L10xW9xD7" (250x225x175mm)
Weight	~4.5 kg

CONNECTORS: REAR PANEL, WATERPROOF

Power	3-pin circular
Data Channels (3) and sensor power	14-pin Circular
Auxiliary Channels	10-pin Circular
RS485 port	Optional 6-pin Circular
GPS	6-pin Circular

CONNECTORS: MAIN PANEL

To PC Keyboard	PS/2 Mini-DIN
To external PC	RS232 (DB9)

Specifications subject to change without notice
105-F West Dudleytown Road, Bloomfield, CT 06002 **USA**
Tel: 1-860-242-8177 Fax: 1-860-242-7812

01/06

e- mail:sales@pmdsci.com Web Site: www.pmdsci.com